



**Univar USA Inc.**  
**6100 Carillon Point**  
**Kirkland, WA 98033**  
**(425) 889-3400**

For Emergency Assistance involving chemicals call - CHEMTREC (800) 424-9300

---

The Version Date for this MSDS is : 02/27/2002

\*\*\*\*\*  
PRODUCT IDENTIFICATION  
\*\*\*\*\*

PRODUCT NAME: N(R) SODIUM SILICATE SOLUTION

MSDS#: PQN

DATE ISSUED: 08/28/00

SUPERSEDES: 07/31/00

ISSUED BY: 008808

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: N(R) Sodium silicate solution  
Product description: A 3.22 weight ratio sodium silicate, 37.5% solution  
in water  
Manufacturer: PQ Corporation  
P. O. Box 840  
Valley Forge, PA USA  
Phone number: 610-651-4200  
Fax number: 610-651-4504  
In case of emergency call: 1610-651-4200  
For customer service call: 1610-651-4330

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical and Common Name	CAS #	Wt. %	OSHA PEL	ACGIH TL v
Water	7732-18-5	62.5%	Not Established	Not Established
Silicic acid, sodium salt; Sodium silicate	1344-09-8	37.5%	Not Established	Not Established

3. HAZARDS IDENTIFICATION

Emergency Overview: Clear to hazy, colorless, odorless, thick liquid.  
Causes eye, skin, and digestive tract irritation.  
Spray mist causes irritation to respiratory tract.  
High pH is harmful to aquatic life. Noncombustible.

Spills are slippery. Reacts with acids, ammonium salts, reactive metals and some organics.

Eye contact: Causes irritation.

Skin contact: Causes irritation.

Inhalation: Spray mist irritating to respiratory system.

Ingestion: May cause irritation to mouth, esophagus, and stomach.

Chronic hazards: No known chronic hazards. Not listed by NTP, IARC or OSHA as a carcinogen.

Physical hazards: Dries to form glass film which can easily cut skin. Spilled material is very slippery. Can etch glass if not promptly removed.

#### 4. FIRST AID MEASURES

Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: If swallowed, DO NOT induce vomiting. Get medical attention immediately. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person.

#### 5. FIRE FIGHTING MEASURES

Flammable limits: This material is noncombustible.

Extinguishing Media: This material is compatible with all extinguishing media

Hazards to fire-fighters: See Section 3 for information on hazards when this material is present in the area of a fire.

Fire-fighting equipment: The following protective equipment for fire fighters is recommended when this material is present in the area of a fire: chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal protection: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots. See section 8.

Environmental Hazards: Sinks and mixes with water. High pH of this material is harmful to aquatic life, see Section 12. Only water will evaporate from a spill of this material.

Small spill cleanup: Mop up and neutralize liquid, then discharge to sewer in accordance with federal, state and local regulations or permits.

Large spill cleanup: Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent runoff from entering into storm sewers and ditches which lead to natural waterways. Isolate, dike and store discharged material, if possible. Use sand or earth to contain spilled material. If containment is impossible, neutralize contaminated area and flush with large quantities of water.

CERCLA RQ: There is no CERCLA Reportable Quantity for this material. If a spill goes off site, notification of state and local authorities is recommended.

#### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed. Promptly clean residue from closures with cloth dampened with water. Promptly clean up spills.

Storage: Keep containers closed. Store in clean steel or plastic containers. Separate from acids, reactive metals, and ammonium salts. Storage temperature 0-95 C. Loading temperature 45-95 C. Do not store in aluminum, fiberglass, copper, brass, zinc or galvanized containers.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.

Respiratory protection: Use a NIOSH-approved dust and mist respirator where spray mist occurs. Observe OSHA regulations for respirator use (29 C.F.R. 1910.134)

Skin protection: Wear body-covering protective clothing and gloves.

Eye protection: Wear chemical goggles.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Thick liquid. .

Color: Clear to hazy white.

Odor: Odorless or musty odor.

PH.: Approximately 11.3

Specific gravity: 1.39 g/cm<sup>3</sup> (20C), 41 Be, 11.62 lbs/gal

Solubility in water: Miscible.

#### 10. STABILITY AND REACTIVITY

Stability: This material is stable under all conditions of use and storage.

Conditions to avoid: None.

Materials to avoid: Gels and generates heat when mixed with acid. May react with ammonium salts resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc.

Hazardous decomposition products: Hydrogen.

#### 11. TOXICOLOGICAL INFORMATION

Acute Data: When tested for primary eye irritation potential according to OECD Guidelines, Section 405, this material produced corneal, iridal and conjunctival irritation. Some eye irritation was still present 14 days after treatment, although the average primary irritation score had declined from 19.7 after 1 day to 4.0 after 14 days. When tested for primary skin irritation potential, this material produced irritation with a primary irritation index of 3 to

abraded skin and 0 to intact skin. Human experience confirms that irritation occurs when this material gets on clothes at the collar, cuffs or other areas where abrasion may occur. The acute oral toxicity of this product has not been tested. When sodium silicates were tested on a 100% solids basis, their single dose acute oral LD, in rats ranged from 1500 mg/kg to 3200 mg/kg. The acute oral lethality resulted from nonspecific causes. This product contains approximately 37.5% sodium silicate.

**Suhchronic Data:** In a study of rats fed sodium silicate in drinking water for three months, at 200, 600 and 1800 ppm, changes were reported in the blood chemistry of some animals, but no specific changes to the organs of the animals due to sodium silicate administration were observed in any of the dosage groups. Another study reported adverse effects to the kidneys of dogs fed sodium silicate in their diet at 2.4g/kg/day for 4 weeks, whereas rats fed the same dosage did not develop any treatment-related effects. Decreased numbers of births and survival to weaning was reported for rats fed sodium silicate in their drinking water at 600 and 1200 ppm.

**Special Studies:** Sodium silicate was not mutagenic to the bacterium *E. Coli* when tested in a mutagenicity bioassay. There are no known reports of carcinogenicity of sodium silicates. Frequent ingestion over extended periods of time of gram quantities of silicates is associated with the formation kidney stones and other siliceous urinary calculi in humans. Sodium silicate is not listed by IARC, NTP or OSHA as a carcinogen.

## 12. ECOLOGICAL INFORMATION

**Eco toxicity:** The following data is reported for sodium silicates on a 100% solids basis: A 96 hour median tolerance for fish (*Gambusia affinis*) of 2320 ppm; a 96 hour median tolerance for water fleas (*Daphnia magna*) of 247 ppm; a 96 hour median tolerance for snail eggs (*Lymnea*) of 632 ppm; and a 96 hour median tolerance for Amphipoda of 160 ppm. This product contains approximately 37.5% sodium silicate.

**Environmental Fate:** This material is not persistent in aquatic systems, but its high pH when undiluted or unneutralized is acutely harmful to aquatic life. Diluted material rapidly depolymerizes to yield dissolved silica in a form that is indistinguishable from natural dissolved silica. It does not contribute to BOD. This material does not bioaccumulate except in species that use silica as a structural material such as diatoms and siliceous sponges. Where abnormally low natural silica concentrations exist (less than 0.1 ppm), dissolved silica may be a limiting nutrient for diatoms and a few other aquatic algal species. However, the addition of excess dissolved silica over the limiting concentration will not stimulate the growth of diatom populations; their growth rate is independent of silica concentration once the limiting

concentration is exceeded. Neither silica nor sodium will appreciably bioconcentrate up the food chain.  
Physical/Chemical: Sinks and mixes with water. Only water will evaporate from this material.

#### 13. DISPOSAL CONSIDERATIONS

Classification: Disposed material is not a hazardous waste.  
Disposal Method: Neutralize and landfill solids in accordance with federal, state and local regulations. Flush neutral liquid to sewer accordance with federal, state and local regulations and permits.

#### 14. TRANSPORT INFORMATION

DOT UN Status: This material is not regulated hazardous material for transportation.

#### 15. REGULATORY INFORMATION

CERCLA: No CERCLA Reportable Quantity has been established for this material.  
SARA TITLE III: Not an Extremely Hazardous Substance under 302. Not a Toxic Chemical under 313. Hazard Categories under 311/312: Acute  
TSCA: All ingredients of this material are listed on the TSCA inventory.  
FDA: The use of sodium silicate is authorized by FDA as a boiler water additive for the production of steam that will contact food pursuant to 21 CFR 173.310; as a component of zinc-silicon dioxide matrix coatings on food contact surfaces pursuant to 21 CFR 175.390(c); as a GRAS substance when migrating from cotton fabric used in dry food packaging pursuant to 21 CFR 182.70; and as a GRAS substance when migrating to food from paper and paperboard products pursuant to 21 CFR 182.90.

#### 16. OTHER INFORMATION

For Additional Information:  
Contact: MSDS Coordinator - Univar USA  
During business hours, Pacific Time - (425) 889-3400

#### NOTICE

Univar USA, expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information refer to a Product Specification Sheet and/or a Certificate of Analysis. These can be obtained from your local Univar USA Sales Office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar USA makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar

USA's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

END OF MSDS